



## Eurotrac

Stougjesdijk 153 3271KB  
Mijnsheerenland NL  
[info@eurotrac.nl](mailto:info@eurotrac.nl)  
+31 (0) 186 612333

## EUROTRAC W12 CMF

The Eurotrac W12-CMF for agricultural and industrial use

Fitted as standard with:



- Yanmar Stage-V engine
- 3 Cylinder, 44 HP
- Joystick controls
- Extra hydraulic function on joystick
- Quick coupler
- Hydrostatic with 2 travel speeds
- Heavy duty axles with hub reduction
- LED lights/working lights
- Wide tyres 19.0/45-17

€34,400.00

## Specifications

### ELECTRICAL INFORMATION

|                  |      |
|------------------|------|
| Battery capacity | 70   |
| Electric system  | 12 V |

### ENGINE

|              |        |
|--------------|--------|
| Cooling      | Liquid |
| Engine power | 44     |

### HYDRAULIC SYSTEM

|           |         |
|-----------|---------|
| Oil yield | 50      |
| Workload  | 180 bar |



### OTHER

|             |    |
|-------------|----|
| Diesel tank | 45 |
| Hydro tank  | 40 |

**WEIGHT**

|                                             |         |
|---------------------------------------------|---------|
| Lifting frame horizontal & machine straight | 1550    |
| Lifting frame horizontal & machine tilted   | 1000 kg |
| Max. Lifting capacity                       | 2000    |
| Own weight                                  | 2620    |

**Technical drawing**



|                                          |      |
|------------------------------------------|------|
| (A) Overall length with bin              | 4650 |
| (B) Overall length without bin           | 3720 |
| (C) Bin pivot                            | 710  |
| (D) Cradle base                          | 1730 |
| (E) Rear overhang                        | 1140 |
| (F) Height to top of roof                | 2340 |
| (H) Seat height                          | 1310 |
| (J) Total working height                 | 3200 |
| (K) Max. lifting height                  | 2600 |
| (L) Loading height                       | 2260 |
| (M) Ejection height                      | 1625 |
| (N) Range (m)                            | 550  |
| (O) Digging depth                        | 60   |
| (P) Overall width                        | 1500 |
| (Q) Track width                          | 1040 |
| (S) Ground clearance                     | 255  |
| (T) Outer diameter                       | 3250 |
| (U) Turning circle                       | 2750 |
| (V) Inside turning circle                | 1500 |
| (W) Rotation angle                       | 45   |
| (X) Tilting angle at max. lifting height | 48   |
| (Y) Tipping angle                        | 45   |
| (Z) Tilt-in angle                        | 50   |

## Pictures





