Eurotrac
Stougjesdijk 153 3271KB
Mijnsheerenland NL
info@eurotrac.nl
+31 (0) 186 612333

EUROTRAC T11

The Eurotrac T11 telescopic loader unique in its class

Fitted as standard with:

- 3 cylinder Kubota D1105 engine
- Rops Frame
- Hydraulic quick coupler
- Hydr. extra function
- Hi/Lo
- Telescope
- Seat heating
- Tyre size 26×12-12AS

€24,750.00

Specifications

DIMENSIONS

Bin pivot	320
Cradle base	1275
Digging depth	16
Ejection height	2145
Ground clearance	200
Height to top of roof	2075
Inside turning circle	1045
Loading height	2570
Max. lifting height	2700
Outer diameter	2560
Overall length with bin	3275
Overall length without bin	2605
Overall width	1130
Range (m)	675
Rear overhang	920
Rotation angle	45
Seat height	1030
Tilt-in angle	30
Tilting angle at max. lifting height	42
Tipping angle	35
Total working height	3400
Track width	865
Turning circle	2195

ELECTRICAL INFORMATION

Battery capacity	45
Electric system	12 V

ENGINE

Cooling	Liquid
Engine power	26

HYDRAULIC SYSTEM

Oil yield	39
Workload	200 bar

HYDRAULIC SYSTEM OTHER	
Diesel tank	25
Hydro tank	40

WEIGHT	
Lifting frame horizontal & machine straight	1350
Lifting frame horizontal & machine tilted	700 kg
Max. Lifting capacity	1350
Own weight	1680

Pictures

trac
RED BY KUBOTA