



Eurotrac

Stougjesdijk 153 3271KB

Mijnsheerenland NL

info@eurotrac.nl

+31 (0) 186 612333



EUROTRAC W12 ICS

The Eurotrac W12-ICS for agricultural and industrial use

Fitted as standard with:

- Kubota StageV engine
- Extra hydraulic function on joystick
- Hydraulic quick coupler
- Hydrostatic with 2 travel speeds
- Radio / Fan / Camera
- Heavy duty axles
- Light bar / LED lights
- Wide tyres 31×15.5-15

€29,300.00

Specifications

ELECTRICAL INFORMATION

Battery capacity	60
Electric system	12 V

ENGINE

Cooling	Liquid
Engine power	26

HYDRAULIC SYSTEM

Oil yield	46
Workload	180 bar



OTHER

Diesel tank	45
Hydro tank	40

WEIGHT

Lifting frame horizontal & machine straight	1350
Lifting frame horizontal & machine tilted	840 kg
Max. Lifting capacity	1350
Own weight	2280

Technical drawing



(A) Overall length with bin	4360
(B) Overall length without bin	3235
(C) Bin pivot	704
(D) Cradle base	1600
(E) Rear overhang	1094
(F) Height to top of roof	2225
(H) Seat height	1205
(J) Total working height	2742
(K) Max. lifting height	2200
(L) Loading height	1790
(M) Ejection height	2250
(N) Range (m)	517
(O) Digging depth	65
(P) Overall width	1340
(Q) Track width	980
(S) Ground clearance	230
(T) Outer diameter	2597
(U) Turning circle	3085
(V) Inside turning circle	1419
(W) Rotation angle	45
(X) Tilting angle at max. lifting height	45
(Y) Tipping angle	45
(Z) Tilt-in angle	46

Pictures





